



OptoSupply

Light It Up

3mm Round Orange & Pure Green LED

**OSOPJC3131A
209 Serise**

■Features


- High Luminous LEDs
- 3mm Round Standard Directivity
- Superior Weather-resistance
- UV Resistant Epoxy
- Water Clear Type

• Everlight :209 Serise

■Applications

- Toys
- Games
- Audio
- Other Lighting

■Outline Dimension



■Absolute Maximum Rating

(Ta=25°C)

| Item | Symbol | Value | | Unit |
|----------------------------|------------------|-------------|-----|------|
| | | Orange | PG | |
| DC Forward Current | I _F | 30 | 30 | mA |
| Pulse Forward Current* | I _{FP} | 100 | 100 | mA |
| Reverse Voltage | V _R | 5 | 5 | V |
| Power Dissipation | P _D | 78 | 108 | mW |
| Operating Temperature | T _{opr} | -30~ +85 | | °C |
| Storage Temperature | T _{stg} | -40 ~ +100 | | °C |
| Lead Soldering Temperature | T _{sol} | 260°C /5sec | | - |

*Pulse width Max.10ms Duty ratio max 1/10

■Electrical -Optical Characteristics

(Ta=25°C)


| Item | Symbol | Condition | Min. | Typ. | Max. | Unit |
|---------------------|---------------------|----------------------|------|------|------|------|
| DC Forward Voltage | V _F (OR) | I _F =20mA | 1.8 | 2.1 | 2.6 | V |
| DC Forward Voltage | V _F (PG) | I _F =20mA | 2.8 | 3.1 | 3.6 | V |
| DC Reverse Current | I _R | V _R =5V | - | - | 10 | μA |
| Domi. Wavelength* | λ _D (OR) | I _F =20mA | 600 | 605 | 610 | nm |
| | λ _D (PG) | I _F =20mA | 585 | 590 | 595 | nm |
| Luminous Intensity* | I _V (OR) | I _F =20mA | 750 | 1120 | - | mcd |
| | I _V (PG) | I _F =20mA | 7000 | 8400 | - | mcd |
| 50% Power Angle | 2θ _{1/2} | I _F =20mA | - | 30 | - | deg |

*1 Tolerance of measurements of dominant wavelength is ±1nm

*2 Tolerance of measurements of luminous intensity is ±15%

*3 Tolerance of measurements of forward voltage is ±0.1V

■Directivity



LED & Application Technologies

