


■Features

- High Luminous LEDs
- 10mm Round Standard Directivity
- UV Resistant Epoxy
- Integral Current Limiting Resistor
- TTL Compatible (Requires No External Current Limiter With 5 Volt Supply)
- Cost Effective (Saves Space and Resistor Cost)
- Color Diffused Type (W/M: White Diffused Type)

■Applications

- Status Indicators
- Other Lighting

■Outline Dimension




■Absolute Maximum Rating

(Ta=25°C)

Item	Symbol	Value	Unit
DC Forward Voltage	V _F	7.5	V
Reverse Voltage	V _R	5	V
Power Dissipation	P _D	150	mW
Operating Temperature	Topr	-30 ~ +85	°C
Storage Temperature	Tstg	-40 ~ +100	°C
Lead Soldering Temperature	Tsol	260°C/5sec	-

■Directivity



■Electrical -Optical Characteristics (Ta=25°C)

Part Number	Color			I _F (mA)*			I _v (mcd)*			λD(nm)*			2θ1/2(deg)
				Min	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	Typ.
				V _F = 5V			V _F = 5V			V _F = 5V			
OSW5DKA132A-5V	White	W		-	12	20	1560	2180	-	X=0.27, Y=0.28(CCT:8500-18000)			30
OSM5DKA132A-5V	Warm White	M		-	12	20	1120	1560	-	X=0.45, Y=0.41(CCT:2700-3300)			30
OSB5SAA134A-5V	Blue	B		-	12	20	750	1120	-	465	470	475	30
OSG5DAA134A-5V	Pure Green	PG		-	12	20	1560	2180	-	520	525	530	30
OSY5PAA134A-5V	Yellow	Y		-	12	20	1120	1560	-	585	590	595	30
OSO5PAA134A-5V	Orange	O		-	12	20	1120	1560	-	600	605	610	30
OSR5PAA134A-5V	Red	R		-	12	20	1120	1560	-	620	625	630	30

*1 Tolerance of measurements of chromaticity coordinates is ±10%

*2 Tolerance of measurements of dominant wavelength is ±1nm

*3 Tolerance of measurements of luminous intensity is ±15%

*4 Tolerance of measurements of forward voltage is ±0.1V