

■ Features

- 0.56 Inch Single Digit Display
- Long lifetime operation
- IC compatible
- Low power dissipation
- Black surface & white segment or dot

■ Applications

- Counting device
- Clock

■ Absolute Maximum Rating (Ta=25°C)

Item	Symbol	Value		Unit
		RA/R/O/Y/YG	W/B/G	
DC Forward Current	I _F	20	20	mA
Pulse Forward Current#	I _{FP}	100	100	mA
Reverse Voltage	V _R	5	5	V
Power Dissipation	P _t	44	66	mW
Operating Temperature	T _{opr}	-30 ~ +70		°C
Storage Temperature	T _{stg}	-40 ~ +85		°C
Lead Soldering Temperature(1.6mm from seating plane)	T _{sol}	260°C/5sec		°C

#Pulse width Max.10ms Duty ratio max 1/10

■ Electrical -Optical Characteristics (Ta=25°C)

Part Number	Color			V _F (V)			I _R (μA)	I _v (mcd)			λD(nm)		
				Min.	Typ.	Max.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.
				I _F =20mA			V _R =5V	I _F =20mA					
OSL10564-IW(LW)	White	W		-	3.3	3.6	10	-	65	-	X=0.27 Y=0.28		
OSL10564-IB(LB)	Blue	B		-	3.3	3.6	10	-	50	-	460	470	475
OSL10564-IG(LG)	Pure Green	G		-	3.3	3.6	10	-	200	-	515	520	530
OSL10564-IYG(LYG)	Yellow Green	YG		-	2.2	2.6	10	-	20	-	565	571	575
OSL10564-IY(LY)	Yellow	Y		-	2.1	2.5	10	-	60	-	585	590	595
OSL10564-IO(LO)	Orange	O		-	2.1	2.5	10	-	70	-	600	605	610
OSL10564-IR(LR)	Red	R		-	2.1	2.5	10	-	26	-	625	630	650
OSL10564-IRA(LRA)	High Luminance Red	RA		-	2.1	2.5	10	-	100	-	620	625	630


*1 Tolerance of measurements of chromaticity coordinates is ±10%

*2 Tolerance of measurements of dominant wavelength is ±1nm

*3 Tolerance of measurements of luminous intensity is ±15%

*4 Tolerance of measurements of forward voltage is ±0.1V

■ Picture







■ Package Dimensions and Pin Function

**OSL10564-IX
(Common Anode type)**

Note:

1, Unit : mm (Tolerance: ± 0.25 mm unless otherwise noted)

2, The slope angle of any PIN may be $\pm 5.0^\circ$ Max







**OSL10564-LX
(Common Cathode type)**

Note:

1, Unit : mm (Tolerance: ± 0.25 mm unless otherwise noted)

2, The slope angle of any PIN may be $\pm 5.0^\circ$ Max



LAMP APPLICATION (PB FREE SOLDERJING)

Apply to Display (DIP) SERIES.

Description:


(1) Manual soldering (Solder Iron)

- (1.1) Temperature at tip of the iron: 350°C Max.
- (1.2) It's banned to load any stress on the resin during soldering.
- (1.3) Soldering time: 3sec.Max.(one time only.)
- (1.4) Leave 3mm of minimum distance from the base of the epoxy.

(2) Dip Soldering (Wave Soldering-Solder Bath)

- (2.1) Leave 3mm of minimum distance from the base of the epoxy.
- (2.2) When soldering, do not put stress on the Display during heating.
- (2.3) Cutting the lead frames at high temperatures may cause LED failure.
- (2.4) Never take next process until the component is cooled down to room temperature after reflow.
- (2.5) After soldering, do not warp the circuit board.
- (2.6) The recommended dip soldering profile is the following.

Wave Soldering



Packaging Details

200pcs/Bag

Carton

Dimension (mm)

330*240*340

15Bags/Carton

