


■ Outline Dimension

- High Luminous LEDs
- 3mm Round Standard Directivity
- UV Resistant Epoxy
- Color Diffused




■ Applications

- Background illumination
- Communications equipment
- Low power DC circuits
- General lighting purposes

■Absolute Maximum Rating (Ta=25°C)

Item	Symbol	Value		Unit
		B/PG	YG/Y/O/R	
DC Forward Current	I _F	30	30	mA
Pulse Forward Current#	I _{FP}	100	100	mA
Reverse Voltage	V _R	5	5	V
Power Dissipation	P _D	102	78	mW
Operating Temperature	Topr	-30 ~ +85		°C
Storage Temperature	Tstg	-40~ +100		°C
Lead Soldering Temperature	Tsol	260°C/5sec		-

■ Directivity



#Pulse width Max.10ms Duty ratio max 1/10

■Electrical -Optical Characteristics (Ta=25°C)

Part Number	Color			V _F (V)*1			I _R (μA)	I _v (mcd)*2			λD(nm)*3/CCT(K)*4			θ1/2(deg)
				Min.	Typ.	Max.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	Typ.
				I _F =20mA			V _R =5V	I _F =20mA						
OSB5YU3V64A	Blue	B		-	2.9	3.4	10	330	500	-	465	470	475	60
OSG5TA3V64A	Pure Green	PG		-	2.9	3.4	10	1560	2180	-	520	525	530	60
OSG8HA3V64A	Yellow Green	YG		-	2.1	2.6	10	100	150	-	565	570	575	60
OSY5JA3V64A	Yellow	Y		-	2.1	2.6	10	330	500	-	585	590	595	60
OSO5JA3V64A	Orange	O		-	2.1	2.6	10	330	500	-	600	605	610	60
OSR5JA3V64A	Red	R		-	2.1	2.6	10	330	500		620	625	630	60
OSR6LU3V64A	Red	R		-	2.1	2.6	10	100	150		630	640	650	60

*1 Tolerance of measurements of forward voltage is $\pm 0.1\text{V}$
 *2 Tolerance of measurements of luminous intensity is $\pm 15\%$
 *3 Tolerance of measurements of dominant wavelength is $\pm 1\text{nm}$

